



## EASY AND FAST TO ASSEMBLE

Can be mounted to a variety of different cab designs.



## HEAVY DUTY

Robust air conditioning systems for demanding applications and environments.



## DRIVER COMFORT

Provides maximum comfort by maintaining a comfortable temperature inside the cabin.



## QUALITY

Designed and manufactured in Europe under the quality standards required by ISO 9001 and IATF 16949.



[www.bergstrominc.com](http://www.bergstrominc.com)



### World Headquarters

Rockford, U.S.A.

+ 1 - 815-874-7821

### Europe

Wales, United Kingdom

+ 44 - 144-386-212

Madrid, Spain

+ 34 - 918-775-840

### Asia-Pacific

Changzhou, Jiangsu, China

+ 86 - 519-511-7821



# HVAC SYSTEMS

Heavy Duty System

PASCAL

KELVIN

BSPS-T-HVAC23R1-EN-B



## Suggested Applications



## KEY - FEATURES



Very robust structure



Low maintenance





3 ventilation speeds



Total adaptation to the vehicle


## Multiple mounting positions



## Main advantages:

- Operator comfort – Provides a comfortable cab temperature.
- Perfect match for your vehicle in different voltages (12V/24V) and suited for different cab types.
- Endurance – Designed for vehicles working in demanding and heavy environments.

## PASCAL system



| AC ❄️                                       | HEATER 🔥               |
|---------------------------------------------|------------------------|
| 4 kW<br>13.648 BTU/hr                       | -                      |
| -                                           | 7,5 kW<br>25.59 BTU/hr |
| 12V — 7.8 A/h                               | 12V — 10 A/h           |
| 24V — 4.5 A/h                               | 24V — 5 A/h            |
| 450 m³/h<br>265 SCFM                        |                        |
| 235 x 390 x 135 mm<br>9.21 x 15.3 x 5.29 in |                        |
| 3,8 kg   8.4 lb                             |                        |

## KELVIN system



| AC ❄️                                         | HEATER 🔥                | HVAC<br>AC & HEAT       |
|-----------------------------------------------|-------------------------|-------------------------|
| 6 kW<br>20.810 BTU/hr                         | -                       | 6 kW<br>20.810 BTU/hr   |
| -                                             | 9,5 Kw<br>32.415 BTU/hr | 9,5 Kw<br>32.415 BTU/hr |
| 12V — 21.6 A/h                                | 12V — 21.6 A/h          | 12V — 20 A/h            |
| 24V — 11 A/h                                  | 24V — 11 A/h            | 24V — 10.5 A/h          |
| 780 m³/h<br>460 SCFM                          | 780 m³/h<br>460 SCFM    | 700 m³/h<br>412 SCFM    |
| 360 x 421 x 170 mm<br>14.71 x 16.53 x 6.69 in |                         |                         |
| 5,2 kg   11.4 lb                              | 5 kg   11 lb            | 6,3 kg   14.3 lb        |


+ Add a recommended condenser



KC-750

+ Choose your accessories

### Outlet panels



### Brackets

